REFRACTORY GUNNING MACHINE

REFRA'S ROTARY GUNNING MACHINE

REFRA – 5

We introduce ourselves as Refractory Brick Cutting Machine, Refractory Castable Pan Mixer, and Refractory Gunning Machine manufacturer. We also manufacture Block Cutting Machine, Detergent Powder Mixer Machine, and Powder Mixer Machine. This machine we have developed with the concept of 'ALIVA' Gunning machine ad success fully running.

TECHNICAL SPECIFICATION FOR ROTAR GUNNING MACHINE	
Power	3.7 KW, 5 H.P, 415 Volts 50 Hz, A.c Motor
Gearing Ratio	283 -2
Conveying Distance (DRY)	100 meters vertical/ 200 meters horizontal.
Conveying Distance (WET)	30 meters vertical / 60 meters horizontal.
Air Consumption	5 = 6 cubic meter / minute.
Control Panel	MCB 32 Amps, Emergency Stop Switch, Indicator.
Minimum Operating Pressure	4 Kg2 cm/ 5Kg2cm
Pump	1 H.P, Discharge 30 meter vertically.
Hose Dia Inner	32 mm / 38mm
Maximum Aggregate size	15 mm

Machine Dimension: Height – 1200 mm, Length – 1000 mm, Width – 750 mm.